

# CANCOM MULTI-MODULE 60 SAFETY

# JÖRGENSEN



## INPUTS/OUTPUTS

20 Digital outputs of which  
8 can be configured as PWM outputs  
16 Digital inputs of which  
8 can be configured as  
frequency inputs (up to 255 Hz)  
4 selectable digital inputs or outputs  
8 Analog inputs (0-5V alt 4-20mA)  
1 x reference voltage 5V

## COMMUNICATION

1 x CAN-bus CanCom 2.0 B  
1 x CAN-bus optional, ex J1939, CANopen  
1 x Radio receiver  
433, MHz or 2,4 GHz

## OTHER

Voltage range: 10-30 Volt  
IP-rating: IP69K  
Total load: 20A  
Temp: -30 - +50° C (radio -20 - +50° C)  
Mating contacts: 5810130029 and  
5810130028  
PL-d category 3 for stop function

## CANCOM MULTI-MODULE 60 SAFETY- SAFETY RATED RADIO RECIEVER.

CanCom series includes modules and transmitters for smart control of mobile hydraulics. Now comes a supplement in the form of a compact module with many functions. The module also has a safe shutdown function. (PL d Category 3).

The module is very robust and can withstand a harsh environment in the IP69K protection as the glass-fiber reinforced housing and plug offers. You can then use the high pressure washer with hot water. The housing is also resistant to many of the fluids that may be present in the automotive and industrial sectors.

Along with Jorgensen's other I/O modules and radio transmitters in CanCom series can easily build a complete control system. The control system is robust and especially adapted for use in demanding operating conditions. Examples of machines that can use such a system, hook lifts, cranes, trucks, sludge pump trucks, etc.

**PL-d  
IP69K**

